



SEM Test Compliance Service Co., Ltd.
3/F, Jinbao Commerce Building, Xin'an Fanshen Road,
Bao'an District, Shenzhen, P.R.C

Material Safety Data Sheet

Material Safety Data Sheet

For

Zhuohai Lang Yi Communication Technology Co., Ltd.
Address: Zhuhai Distract Fuyong town of Xinhua District two three Lu Yidong 301
shop, China

and for their product

Li-ion Battery

Model/type reference : LA

Nominal Voltage : 24V

Typical Capacity : 1000mAh


Version number : V1.0

Revision date : N/A

Laboratory	SEM Test Compliance Service Co., Ltd.
Address	3/F Jinbao Commerce Building Xin'an Fanshen Road, Bao'an District Shenzhen, P.R.C. (518101)

Compiled by (name+ signature) Kitty Yang

Approved by (+ signature) Ails Ma



Section 1- Chemical Product and Company Identification



SEM Test Compliance Service Co., Ltd.
3/F, Jinhao Commerce Building, Xinhai Fanchun Road,
Bao'an District, Shenzhen, P.R.C.

Material Safety Data Sheet

Product Identification: Li-Ion Battery

Manufacturer/Supplier Name: Zhuhai Kang Yi Communication Technology Co., Ltd.
Address: Zhuhai District Fuyang town of Zhuhai District two three Lu Yidong 311 shop,
China

Telephone number of the supplier: +86-755-27365362

Emergency Telephone No.(24h): +86-755-27365382
Fax: +86-755-27196536

e-mail address: candy11203@126.com

Preparation Date: Nov. 05, 2011

This MSDS was prepared by SEM Test Compliance Service Co., Ltd.

Item Number: STR10118050S

Referenced documents: ISO 11014:2009 Safety data sheet for chemical products

Section 2 - Hazards Identification

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shred Li-Ion Battery. Exposure to the ingredients contained within or their ingredients products could be harmful.
Appearance, Color, and Odor	Solid object with no odor, no color.
Primary Route(s) of Exposure	These chemicals are contained in a sealed stainless steel enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by inhalation, ingestion, eye contact and skin contact
Potential Health Effects:	ACUTE (short term): see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns. Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation. Ingestion: Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. Skin: Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin. Eye: Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye. CHRONIC (long term): see Section 11 for additional toxicological data



SEM Test Compliance Service Co., Ltd.
3 F, Jinhao Commerce Building, Xixun Fanzhen Road
Bao'an District, Shenzhen, P R C

Material Safety Data Sheet

SEM Compliance

Medical Conditions Aggravated by Exposure	Not applicable
Reported as carcinogen	Not applicable

Section 3 - Composition/Information on Ingredients

This Battery is a mixture.

Hazardous Ingredients (Chemical Name)	Concentration or concentration ranges (%)	CAS Number
Aluminum Foil (Al)	14.30%	7429-90-5
Copper Foil (Cu)	6.38%	7440-50-8
SEI (C ₆ H ₆ , C ₆ H ₄) _n	0.61	61789-96-6
Lithium Cobalt Oxide (Li CoO ₂)	31.92%	12190-79-3
Graphite powder (C)	14.6%	7782-42-5
Rubber	8.36%	69028-37-1
Carbon black	0.8%	1333-86-4
Polypropylene	1.84	9003-07-0
Polyethylene	1.37	9002-88-4
Lithium hexafluoroarsenate (LiPF ₆)	1.31	21324-40-3
Ethylene carbonate (EC)	4.26%	96-49-1
Diethyl carbonate (DEC)	9.23%	105-58-8
Propylene carbonate (PC)	0.81	108-32-7
Nickel	1.11	7440-02-0

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4 - First-aid Measures

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice.
------------	--



SEM Test Compliance Service Co., Ltd.
3/F, Jinbao Commerce Building, Xin'an Fanshen Road,
Bao'an District, Shenzhen, P.R.C

Material Safety Data Sheet

Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

Section 5 - Fire-fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contain within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
Suitable extinguishing Media	Use <i>extinguishing media</i> suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases Sensitivity to Static Discharge: Not Applicable
Specific Hazards arising from the chemical	Fires involving Li-Ion Battery can be controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0



SEM Test Compliance Service Co., Ltd.
3/F, Jinhao Commerce Building, Xixiang Road, Xixiang
Bao'an District Shenzhen, P.R.C

Material Safety Data Sheet

Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7 – Handling and Storage

Handling	Don't handling Li-Ion Battery with metalwork. Do not open, disassemble, crush or burn battery. Ensure good ventilation/ exhauston at the workplace. Prevent formation of dust Information about protection against explosions and fires: Keep ignition sources away- Do not smoke.
Storage	If the Li-Ion Battery are subject to storage for such a long term as more than 3 months, It is recommended to recharge the Li-Ion Battery periodically. 3 months: -10°C~+40°C, 45 to 85%RH And recommended at 0°C~+35°C for long period storage. The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more. The voltage for a long time storage shall be 3.7V~4.2V range. Do not storage Li-Ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.



SEM Test Compliance Service Co., Ltd.
3/F, Jintao Commerce Building, Ximen Fanshen Road
Bao'an District, Shenzhen, P.R.C

Material Safety Data Sheet

	Keep out of reach of children. Do not expose Li-ion Battery to heat or fire Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials.
--	---

Section 8 – Exposure Controls and Personal Protection

Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery. Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

Section 9 - Physical and Chemical Properties

Physical State	Form: Solid
	Color: Black
	Odour: Monotony
Change in condition:	
pH, with indication of the concentration	Not applicable
Melting point/freezing point	Not available.
Boiling Point, initial boiling point and Boiling	Not available.



SEM Test Compliance Service Co., Ltd.
3F, Jindao Commerce Building, Xixian Fenshen Road
Bao'an District, Shenzhen, P.R.C

Material Safety Data Sheet

range:	
Flash Point	Not available
Upper/lower flammability or explosive limits	Not available
Vapor Pressure:	Not applicable
Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.
Solubility in Water:	Insoluble
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	130°C
Decomposition temperature	Not available.
Odour threshold	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Viscosity	Not applicable

Section 10 - Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Li-Ion Battery to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not Available

Section 11 - Toxicological Information

Irritation	Risk of Irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, Irritation to the skin, eyes and respiratory tract may occur.
------------	--



SEM Test Compliance Service Co., Ltd.
3F. Jincuo Commerce Building Xian FanShen Road
Bao'an District Shenzhen, P.R.C

SEM Test Compliance

Material Safety Data Sheet

Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

Section 12 - Ecological Information

General note	Water hazard class 1 (Self-assessment) slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water water course or sewage system
Anticipated behavior of a chemical product in environment/possible environmental impact/ecotoxicity	Not Available
Mobility in soil	Not Available
Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available

Section 13 - Disposal Considerations

Product disposal recommendation: Observe local state and federal laws and regulations
Packaging disposal recommendation: Be aware discarded batteries may cause fire. Tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local state and federal laws and regulations.

Section 14 - Transport Information

The Li-ion Battery () had passed the test UN 38.3 and are classified as non-dangerous goods. Concorde's Li-ion batteries comply with the UN Recommendations on the Transport of Dangerous Goods, IATA Dangerous Goods regulations and applicable U.S. DOT regulations for the safe transport of Li-ion Battery.

Li-ion Battery is complied with Section II of PI965-PI957

